

EF-3

Utility Flashlight

The DME EF-3 is a standard hand-held utility flashlight that operates with "D" cell batteries. The optional 9G mounting bracket makes the EF-3 easy to install on walls, bulkheads, and partitions in aircraft.



Power Source

- Two standard "D" cell batteries

Part Numbers

Description

- Model EF-3 Flashlight
- Model EF-3 System
- Optional Bracket

Part Number

- P2-07-0012-001
- P2-07-0013-002
- P2-07-0006-001

System Size and Weight

10.125 in L x 2.75 in W x 3.00 in H
(257.2 mm L x 69.9 mm W x 76.2 mm H)

1.39 lbs (.63 kg) nominal

Specifications

- Light operating time: 2 hours of illumination (to 500 fc @ 20°C)
- Light output: approximately 950 candela
- Operating temperature: -20°C to 54°C (-4°F to 129.2°F)

Certification

FAA-PMA

KEY BENEFITS

- Constructed with ABS flame retardant material, the EF-3 conforms to FAR 25.853(a), FAR 121.549(b), FAR 121.310(n) and applicable SAE, ATA, and military specifications.
- System includes a self-cleaning switch.
- Flashlight includes a rewritable RFID tag.

ORDERING INFO

130 Commerce Way
East Aurora, NY 14052 USA
+1.716.655.0800
LSINYSales@astronics.com
astronics.com/emergencysystems